Printed in China VN:EN-PC-201607-01

ZOOMLION

Zoomlion Heavy Industry Science & Technology Co. ,Ltd.
Add:No.677 Lugu Road Zoomlion Industrial Park Changsha,Hunan,China,410205

Copyright© 2016 Zoomlion.All rights reserved.Reproduction and copying of any part of the contents is not allowed for any purposes without Zoomlion 's written approval.
Note:No product coating appearance shall be subject to sample.

CONCRETE TRAILER PUMP

ZOOMLION

Main Parameters

Item \ Model		HBT40.10.60RS	HBT60.13.90SU
Pumping system			
Max. theoretical output	m^3/h	49/26	67/41
Max. theoretical pressure on concrete	MPa	5/10	7/13
Concrete cylinder (diam.×stroke)	mm	Φ 180×1250	Φ 200×1800
Hopper capacity×feeding height	L×mm	500×1335	600×1450
Power system			
Engine model		Diesel 4BTA3.9-C80	Electric YE2-280M-4
Rated power	kW	60	90
Rated speed	r/min	2200	1485
Main configuration			
Inside diameter of delivering pipe	mm	Φ 125/ Φ 150	Φ 125/ Φ 150
Dimensions (length×width×height)	mm	5300×2020×2550	7000×2200×2300
Total weight	kg	4500	6960

Technical data and characteristics subject to modifications without notice.

Main Parameters

Model / Item		HBT80.14.174RSU	HBT100.18.186RSU
Pumping system			
Max. theoretical output	m^3/h	85/55	93/54
Max. theoretical pressure on concrete	MPa	8/14	10/18
Concrete cylinder (diam.×stroke)	mm	Φ 200×1800	Φ 200×1800
Hopper capacity×feeding height	L×mm	600×1450	600×1450
Power system			
Engine model		Diesel BF6M1013-24T3R/2	Diesel BF6M1013-25T3R/1
Rated power	kW	174	186
Rated speed	r/min	2300	2100
Main configuration			
Inside diameter of delivering pipe	mm	Φ 125/ Φ 150	Φ 125/ Φ 150
Dimensions (length×width×height)	mm	7000×2200×2750	7500×2200×2750
Total weight	kg	7300	7900

Technical data and characteristics subject to modifications without notice.

Model / Item		HBT105.21.273RSD	HBT110.26.372RS
Pumping system			
Max. theoretical output	m^3/h	105/65	112/73
Max. theoretical pressure on concrete	MPa	13/21	16/26
Concrete cylinder (diam.×stroke)	mm	Φ 200×2100	Φ 200×2100
Hopper capacity×feeding height	L×mm	800×1400	800×1410
Power system			
Engine model		Diesel TCD 2015 V06	Diesel BF6M1013-25T3R/1
Rated power	kW	273	2×186
Rated speed	r/min	2100	2100
Main configuration			
Inside diameter of delivering pipe	mm	Φ 125/ Φ 150	Φ 125
Dimensions (length×width×height)	mm	7200×2250×2940	7700×2300×2800
Total weight	kg	9700	13000

Technical data and characteristics subject to modifications without notice.

Perfect Quality Guarantee

High Precision Machining Production Line



Advanced Testing Center

Standard 6S Logistics and Warehousing

Well-known Cases

Qingzang Railway Construction Site

Chongqing LRT

Gate of the Orient,Suzhou Construction Site

Kingkey Financial Center Construction Site,Shenzhen

Construction Site of West Tower of Zhujiang NewCity,Guangzhou

Tallest Building in Chongqing

CCTV New Site Construction Site